



LS 01
LS 02
LS 03

Available colours



Special colour additives

LS are innovative colour additives that have been developed to create eye-catching and unique colour effects. These products are particularly suited for use with solvent mixing systems, and they can be used to recreate difficult-to-reproduce colours from brands such as Mazda. The **LS line** comprises three unique colour mixes that can be used to express individuality and create a truly distinct visual experience. These products have been developed with the aim of surprising audiences and achieving stunning visual effects.

LS is available in convenient 1-Litre tins, making it suitable for both small and large-scale applications. With its innovative colour technology, **LS** is an excellent addition to any paint system

PACKAGING	
Volume	Collective packaging
1 l	3 pcs.



INTERESTING
COLOURS



SATURATED AND
VIVID COLOURS



INDIVIDUAL
COLOURS



ADDED TO
BASECOAT



RECOMMENDED SIZES
FOR PAINT STRAINER
125-190 µm



PAINT EFFICIENCY
according to the colour



COLOURS AVAILABLE:

- LS 01 Liquid Silver
- LS 02 Blue Metallic
- LS 03 Glass Effect



MODEL APPLICATION

- step I
black acrylic primer coating
(e.g. **S72**)
- step II
coating according to formula
e.g. **Mazda 46G**
- step III
clearcoat application



MINIMUM SHELF LIFE

36 months in originally sealed
packaging



SUBSTRATE PREPARATION

Once the suitable primer coat has
been abraded, clean using silicone
remover **CP 015** in preparation to
apply basecoat



MIXING RATIO

LS is added to the solvent base.
For OEM codes, the amount of additive
is determined by the recipe in the recipe
software



SPRAY GUN SETTINGS

Nozzle size: **1.2-1.4 mm**;
Operating pressure: HVLP/RP **1.8-2.0 bar**



APPLICATION

Application is subject to the specific
method and colour that the additive
is used with



EVAPORATION TIME
AFTER APPLICATION

5-10 min after application at **20°C**
and **65%** relative humidity

PROCESS

PROCESS

PROCESS