

CP 333



Available colours



UNI+ polyester putty

CP 333 Universal Polyester Putty stands as a high-strength filler designed for versatile surface shaping. This putty provides excellent adhesion to various substrates and is characterized by its ease of application and processing.

However, it's important to note that **CP 333** cannot be used on surfaces in direct contact with foodstuffs and drinking water. Conveniently available in a 2 kg package, **CP 333** offers a practical solution for a range of surface shaping applications, ensuring strength and reliability in use.

PACKAGING	
Volume	Collective packaging
2 kg + 40 g hard.	4 pcs. + 4 pcs.



EASY TO PROCESS



ADHESION



HIGH DURABILITY



POT LIFE

5-6 min after mixing with hardener



MINIMUM SHELF LIFE

12 months in originally sealed packaging



VOC

2004/42/WE IIB(b) (250) 45

PROCESS

PROGRESS

PROGRESS



SUBSTRATE PREPARATION

The product is applied to a previously sanded and cleaned substrate. Old coatings should be removed. The most effective method is application on an epoxy primer **CP 394**. Do not apply putty on top of reactive primer



MIXING RATIO

100 parts of **CP 333**

Hardener:

- < **10°C** - **3-3.5%**
- **10-20°C** - **2-2.5%**
- > **20°C** - **11.5%**



APPLICATION

Application in several thin coats. After each of these, the product should be cured



MIXING BEFORE USE

The product must be mixed before and after adding the hardener



DRYING

Drying times at **20°C** and **65%** relative humidity:
- **20-30 min**



IR DRYING

~**5 min**, do not exceed **80°C**



GRINDING

Coarse (dry): **P100-P120**
Finishing (dry): **P120-P240**