



CP 066

Fade-out thinner

CP 066 is a specialized thinner designed for blending two-component products, dedicated for both two-coat and single-coat bodywork methods. Its application is particularly effective for creating a blending effect (partial painting of the vehicle) with **ACRYL** pigment paint or clearcoat.

Best suited for precision work, **CP 066** excels in painting small areas, making it ideal for intricate applications like "smart" repairs. This product is available in practical 1-Litre tins, providing a convenient solution for precision painting needs.

PACKAGING	
Volume	Collective packaging
1 l	6 pcs.



EFFICIENT



FOR 2K PRODUCTS



SPRAY VISCOSITY

11-12 sec. DIN Flow Cup 4 mm



RECOMMENDED SIZES FOR PAINT STRAINER

190 µm



POT LIFE

Ready-to-use product



MINIMUM SHELF LIFE

24 months in originally sealed packaging



SUBSTRATE PREPARATION

The transition area is abraded with **P1500-P2000** grade paper or grey fleece with matting paste. Degrease the surface with silicone remover



MIXING RATIO

70 parts of **CP 066**
30 parts of 2K product



SPRAY GUN SETTINGS

Nozzle size: **1.2-1.4 mm**;
Operating pressure: HVLP/RP **1.8-2.0 bar**



APPLICATION

One coat is applied in several centimetre-long strips. The best effect is achieved with a small admixture of topcoat. It needs polishing after drying



EVAPORATION TIME AFTER APPLICATION

~4 min after coating at **20°C** and **65%** relative humidity



DRYING

Drying times at **20°C** and **65%** relative humidity: **~10-20 min**