

CP 334



Available colours

Soft Plus polyester putty

CP 334 Soft Plus multi-purpose polyester putty seamlessly combines the attributes of a filling putty with those of a finishing putty. Renowned for its excellent adhesion to various substrates, it adeptly fills both large irregularities and small cavities. Easy to apply and can be abraded with coarse and fine papers, **Soft Plus** ensures a very smooth surface without holes, minimizing the necessity for unnecessary sanding.

It's important to note that this putty must not be used on surfaces in direct contact with foodstuffs and drinking water. Available in 1 and 1.8-kilogram packs, **CP 334 Soft Plus** provides a versatile solution for a variety of filling and finishing applications, ensuring a high-quality surface finish.

PACKAGING	
Volume	Collective packaging
1 kg + 20 g hard.	4 pcs. + 4 pcs.
1.8 kg + 40 g hard.	4 pcs. + 4 pcs.



EASY TO PROCESS



GOOD ADHESION



SMOOTH SURFACE



HIGH DURABILITY



FIRM FILLING



POT LIFE

5-6 min after mixing with hardener



MINIMUM SHELF LIFE

12 months in originally sealed packaging



VOC

2004/42/WE IIB(b) (250) 61

PROCESS

PROCESS

PROCESS



SUBSTRATE PREPARATION

The product is applied to a previously sanded and cleaned substrate. Old coatings should be removed. The most effective method is application on an epoxy primer **CP 394**. Do not apply putty on top of reactive primer



MIXING RATIO

100 parts of **CP 334**

Hardener:

- < 10°C - 3-3.5%
- 10-20°C - 2-2.5%
- > 20°C - 11.5%



APPLICATION

Application in several thin coats. After each of these, the product should be cured



MIX BEFORE USE

The product must be mixed before and after adding the hardener



DRYING

Drying times at 20°C and 65% relative humidity:
- 20-30 min



IR DRYING

~5-10 min, do not exceed 80°C



GRINDING

Coarse (dry): **P100-P120**
Finishing (dry): **P120-P240**