

CP 490



Elastic additive

The **Elastic Additive** serves a specific purpose in painting vehicle components constructed from flexible plastics. It's indispensable for 2K paints and primers that demand special additives. By incorporating **CP 490** into clearcoats and two-component primers, it enhances the coating's flexibility, effectively preventing cracks in the paintwork.

Available in containers of 0.25, 0.5, and 1-Litre volumes, this product offers flexibility in usage and application quantities to suit varied project needs.

PACKAGING	
Volume	Collective packaging
0.25 l	10 pcs.
0.5 l	6 pcs.
1 l	6 pcs.



IMPROVE FLEXIBILITY



PREVENTS FORMATION OF CRACKS



EXTENDS THE DRYING TIME OF THE PAINTED COATING



POT LIFE
Ready-to-use product



APPLICATION
- acrylic primer
- clearcoat
CP 490 is particularly suitable for fast-drying products (**CP 365**, **CP 375**, **CP 1800**, **CP 2015**)



MINIMUM SHELF LIFE
24 months in originally sealed packaging

PROCESS



MIXING RATIO
100 parts of primer or of acrylic clearcoat
20-50 parts of **CP 490** (thinner not to be added)



SPRAY GUN SETTINGS
According to method



APPLICATION
According to method



DRYING
Special attention must be paid to high temperatures when drying plastic parts. Addition of **CP 490** extends the drying process

PROGRESS

↓