

## CP 339



Available colours



### Light polyester putty

**Perfectly Light** is a light olive-coloured polyester filler putty meticulously crafted for the repair of car body parts. With its low weight, the product avoids imposing excess weight on the surface to be repaired, particularly on horizontal elements like the roof. The putty is easily applicable and sandable, suitable for application on steel, aluminum, galvanized substrates, GRP/GRP laminates, polyester putties, acrylic and epoxy primers, and old paint coatings. Conveniently available in a 1-Litre package, **Perfectly Light** offers a practical solution for achieving efficient and lightweight repairs across various automotive substrates.

PACKAGING	
Volume	Collective packaging
1 l + 20 g hard.	4 pcs. + 4 pcs.



LIGHT PUTTY



EASY TO PROCESS



EASY TO APPLY



SMOOTH SURFACE



GOOD ADHESION



#### POT LIFE

7-8 min after mixing with hardener



#### MINIMUM SHELF LIFE

12 months in originally sealed packaging



#### VOC

2004/42/WE IIB(b) (250) 44

PROCESS

PROGRESS

PROGRESS



#### SUBSTRATE PREPARATION

The product is applied to a previously sanded and cleaned substrate. Old coatings should be removed. The most effective method is application on an epoxy primer **CP 394**. Do not apply putty on top of reactive primer



#### MIXING RATIO

**100 parts** of **CP 339**  
Hardener: **2%**



#### APPLICATION

Application in several thin coats. After each of these, the product should be cured



#### MIXING BEFORE USE

The product must be mixed before and after adding the hardener



#### DRYING

Drying times at **20°C** and **65%** relative humidity:  
- **20-30 min**



#### IR DRYING

~**10-12 min**, do not exceed **80°C**



#### GRINDING

Coarse (dry): **P100-P120**  
Finishing (dry): **P120-P280**