



Candy

Available colours



Special colour additives

The **Candy** additives are a range of high-quality products that can be added to a solvent basecoats to achieve complex, unique and original colours. This includes difficult-to-reproduce colours such as Mazda 46V and Renault NNP, as well as a range of individual colours that can be achieved by using these additives. In addition to providing exceptional colour options, the **Candy** additives are also ideal for achieving interesting visual effects. For this reason, they are popular among airbrush painters who are looking to create unique and visually stunning pieces. The **Candy** additives are available in convenient 0.5-Litre tins, making them an excellent choice for both small and large-scale painting projects. With their high-quality formulation and exceptional colour options, the **Candy** additives are a must-have for any professional painter or hobbyist looking to achieve stunning and original colour effects.

PACKAGING	
Volume	Collective packaging
0.225 l	6 pcs.



SOLVENT ADDITIVE



PAINT EFFICIENCY



SATURATED AND
VIVID COLOURS



INDIVIDUAL
COLOURS



CONVENIENT
PACKAGING



RECOMMENDED SIZES
FOR PAINT STRAINER
125-190 µm



PAINT EFFICIENCY
according to the colour



COLOURS AVAILABLE:

- C20 yellow
- C30 orange
- C40 red
- C50 blue
- C70 black



MODEL APPLICATION

- step I
silver acrylic primer coating
(M9-0306.0)
- step II
coating with a mixture of base
resin B01 and Candy (e.g. 90%
B01 + 10% Candy C50)
- step III
coat application



MINIMUM SHELF LIFE

36 months in originally sealed
packaging



VOC

2004/42/WE IIB (840) 820



SUBSTRATE PREPARATION

Once the suitable primer coat has
been abraded, clean using silicone
remover CP 015 in preparation to
apply basecoat



MIXING RATIO

Candy is added only to solvent based
mixing systems.
For OEM codes, the amount of additive
is determined by the recipe found in the
formulation software. In case of custom
colours, a maximum of **30%** of **Candy** is
added



SPRAY GUN SETTINGS

Nozzle size: **1.2-1.4 mm**;
Operating pressure: HVLP/RP **1.8-2.0 bar**



APPLICATION

Application is subject to the specific
method and colour that the additive
is used with



EVAPORATION TIME
AFTER APPLICATION

5-10 min after coating at **20°C**
and **65%** relative humidity

PROCESS

PROGRESS

PROGRESS