

CP 341



Available colours



Plastic putty

CP 341 Plastic is a specialized polyester putty crafted for use on plastics. Characterized by high flexibility and ease of application, it yields a remarkably smooth surface. This putty is suitable for application on surfaces made of various plastics, including PP, EPDM, ABS, PC, PPO, and PA.

Available in a convenient 1 kg package, **CP 341 Plastic** provides a practical solution for effectively repairing and refining plastic surfaces, ensuring flexibility and a smooth finish.

PACKAGING	
Volume	Collective packaging
1 kg + 20 g hard.	4 pcs. + 4 pcs.



FLEXIBLE



EASY TO APPLY



EASY TO PROCESS



BLACK COLOUR



VERY SMOOTH SURFACE



POT LIFE

3-4 min after mixing with hardener



MINIMUM SHELF LIFE

12 months in originally sealed packaging



VOC

2004/42/WE IIB(b) (250) 26



SUBSTRATE PREPARATION

The product is applied to a previously sanded maroon fleece surface. Then it should be degreased with **CP 015** remover, and cleaned with **CP 011** remover. Before its application, it is necessary to discharge the electrostatic voltage of **CP 012**



MIXING RATIO

100 parts of **CP 341**
Hardener: **2%**



APPLICATION

Before starting work, it is recommended that the components are warmed up. Application in several thin coats. The product should be cured after application of each one. Do not exceed 3 mm thickness



MIXING BEFORE USE

The product must be mixed before and after adding the hardener



DRYING

Drying times at **20°C** and **65%** relative humidity:
- **20-25 min**



IR DRYING

no applicable



GRINDING

Coarse (dry): **P100-P120**
Finishing (dry): **P120-P320**

PROCESS

PROGRESS