

WLS 02 WLS 03

WLS are innovative color additives designed to create striking and unique visual effects. These products are specifically developed for waterborne mixing systems and can be used to reproduce challenging colors from brands like Mazda. The **WLS** line consists of two distinct mixes, offering a creative way to enhance individuality and achieve remarkable finishes. Designed to surprise and captivate, **WLS** brings advanced color technology to

Available in 0,25-liter tins, it is a versatile solution for both custom and professional

PACKAGING

INDIVIDUAL

COLOURS

SATURATED AND

VIVID COLOURS

Collective packaging

6 pcs.

ADDED TO

BASECOAT



any paint system.

Volume

0,251

INTERESTING

COLOURS

applications.

new



RECOMMENDED SIZES FOR PAINT STRAINER 125 µm

PAINT EFFICIENCY according to the colour



COLOURS AVAILABLE: - WLS 02 Blue Metallic - WLS 03 Glass Effect

ر) ⊒⊐ <u>77</u>	
/\	

MODEL APPLICATION

step I coating according to formula e.g. **Nissan KBZ** step II clearcoat application



MINIMUM SHELF LIFE

24 months in originally sealed packaging

	SI
(♦`♦)	Or
	be
	rer

PROCESS

V

PROGRESS

SUBSTRATE PREPARATION

Once the suitable primer coat has been abraded, clean using silicone remover **CP 015** in preparation to apply basecoat

MIXING RATIO

WLS is added to the waterborne system. For OEM codes, the amount of additive is determined by the recipe in the recipe software

SPRAY
Nozzle si Operatinę

SPRAY GUN SETTINGS

Nozzle size: **1.2-1.4 mm**; Operating pressure: HVLP/RP **1.8-2.0 bar**

FA	APPL
楽)	Applica
	methor

APPLICATION

Application is subject to the specific method and colour that the additive is used with



EVAPORATION TIME AFTER APPLICATION

10-15 min after application at 20°C and 65% relative humidity